

W e l c o m e t o t h e w o r l d o f B i g B a g s



Ecotainer 4 corner loops FIBC

Ecotainer 4 corner loops FIBC

Characteristics

The four loops are fixed by overlock sewing or with chainstitch or with a combination of both along the FIBC. The long seam along the edge of the bag gives a very good distribution and guarantees, a high tenacity and high S.W.L. (safe working load) for these bags.

Advantage

This type is the number one in the category of 4 loop FIBC's worldwide. This is because of the economic production method and the good tenacity of these bags. A simple design which saves you money.

Features

Based on the above bag construction we produce a variety of special FIBC's:

- coated, uncoated and coated sandwich fabric.
- form-stable Q-bags.
- with safety factor 5:1, 6:1 and 8:1.
- UN-approved bag with safety factor (SF) 6:1.
- conductive or antistatic approved.
- siftproof and super siftproof.
- with liner in special qualities, (e.g. PE, PP, laminated, coex, etc), cleared, coloured, suspended or glued.
- with pop-up reinforcements loop in loop version and stevedore straps, a perimeterband can be sewn around the top of the bag over the loops.

- all bags can be printed in multi-colour and can be supplied with a large variety of document-pouches and labels.
- a range of additional features.

Dimension

- A variety of possible dimensions (minimum base 70 cm x 70 cm and maximum 110 cm x 110 cm).
- Any other dimensions can be tailored.

